

SOLPED 1000123270 - Evaluación N° SEL-0032-2024-OTL/PP. Primera Convocatoria.
"ADQUISICIÓN DE MANGUERAS PARA DRENAJES PLUVIALES DE TANQUES
EN REFINERÍA TALARA"

Item	DESCRIPCION	POSTOR 1		POSTOR 2	
		ABUGATTAS & PERATA INTERNACIONAL S.A.C.		GLOBAL SUPPLY COMPANY S.A.C.	
		10894-2024		GSCo 610.032.OTL24	
		Propone	Observaciones	Propone	Observaciones
1.1	19-100-129890 HOSE TANK ROOF FLOATING. ASSEMBLY DRAIN WATER. ----- NOMINAL SIZE 3 INCHES DIA X 35 FEET LENGTH. MAX WORK PRESSURE: 150 PSI / 10 BAR MAX WORK TEMPERATURE: 100 DEG CELSIUS. ENDS WITH NIPLES AND INTEGRATED FLANGE 3 INCHES X 150 CLASS ANSI B16.5. CONSTRUCTION: INNER TUBE OF NEOPRENE OR NITRILE RESISTANT TO CRUDE PETROLEUM OILS, COVER DESIGNED OF VITON TO RESIST IMMERSION IN 100 % AROMATIC WITH REINFORCING STAINLESS STEEL ARMoured WIRE HELIX; ASSEMBLY FITTED INCLUDES BALLAST CABLE WITH LEAD FERRULE TO ENSURE NEGATIVE BUOYANCY. ELECTRICAL CONTINUOUS. ANTISTATIC. FACTORY APPLIED LONGITUDINAL COLOURED STRIPE TO ENSURE CORRECT ALIGNMENT. CLAMPS AND CHAIN FOR ROOF ATTACHMENT HYDROSTATIC FACTORY TESTED AND CERTIFIED.	SI CUMPLE REQUISITOS MINIMOS	NINGUNA	SI CUMPLE REQUISITOS MINIMOS	NINGUNA
1.2	19-100-129895 HOSE TANK ROOF FLOATING. ASSEMBLY DRAIN WATER. ----- NOMINAL SIZE 4 INCHES DIA X 95 FEET LENGTH. MAX WORK PRESSURE: 150 PSI / 10 BAR MAX WORK TEMPERATURE: 100 DEG CELSIUS. ENDS WITH NIPLES AND INTEGRATED FLANGE 4 INCHES X 150 CLASS ANSI B16.5. CONSTRUCTION: INNER TUBE OF NEOPRENE OR NITRILE RESISTANT TO CRUDE PETROLEUM OILS, COVER DESIGNED OF VITON TO RESIST IMMERSION IN 100 % AROMATIC WITH REINFORCING STAINLESS STEEL ARMoured WIRE HELIX; ASSEMBLY FITTED INCLUDES BALLAST CABLE WITH LEAD FERRULE TO ENSURE NEGATIVE BUOYANCY. ELECTRICAL CONTINUOUS. ANTISTATIC. FACTORY APPLIED LONGITUDINAL COLOURED STRIPE TO ENSURE CORRECT ALIGNMENT. CLAMPS AND CHAIN FOR ROOF ATTACHMENT HYDROSTATIC FACTORY TESTED AND CERTIFIED.	SI CUMPLE REQUISITOS MINIMOS	NINGUNA	SI CUMPLE REQUISITOS MINIMOS	NINGUNA
Aprobado por Coordinación Optimización Monitoreo y Control Jefatura Ingeniería de Mantenimiento		SI CUMPLE REQUISITOS MINIMOS		SI CUMPLE REQUISITOS MINIMOS	